



- · Joins threaded ports to a flange style connection
- · Often used to join the NPT port of a static transmitter with a flange mounted connection on a differential pressure to static adapter plate
- · Available in Zinc-Nickel plated Steel and electropolished 316 Stainless Steel

SPECIFICATIONS		
Materials	Zinc-Nickel plated Steel, 316 Stainless Steel*	
Connections	1/2" NPT Male-flange, 1/2" NPT Female-flange	

* All 316SS products meet the requirements of NACE MR0175/ISO 15156-3.

For NOSHOK Steel Static Adaptors:



WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For NOSHOK Stainless Steel Static Adaptors:




WARNING: This product can expose you to chemicals including Chromium (VI) and Nickel, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



ORDERING INFORMATION			
SERIES	SA Static adaptor		
MATERIALS	C Steel	S 316 Stainless Steel	
CONNECTIONS	1 1/2" NPT Female - Flange	2 1/2" NPT Male - Flange	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.



Static Adaptor, Female NPT

