

Dial Indicating Pressure Gauges Options Stock Lists

Stock Item Denoted by Shaded Background

MISCELLANEOUS OPTIONS

| OPTIONS | | COMMENTS |
|--|----------------------|--|
| CERTIFIED CALIBRATION (CC) | | AGAINST PRIMARY STANDARD TRACEABLE TO NIST |
| PRESSURE RANGE | ACCURACY | |
| Vacuum through 15,000 psi | ±0.25% through ±2.5% | |
| 20,000 psi through 40,000 psi | ±0.5% through ±2.5% | |
| | ±0.25% | |
| 60,000 psi through 80,000 psi | ±0.25% through ±2.5% | |
| 100,000 psi | ±0.25% through ±2.5% | |
| INCREASED GAUGE ACCURACY FROM ±1.5% TO ±1.0% | | |
| INCREASED GAUGE ACCURACY FROM ±1.0% TO ±0.5% | | |
| CERTIFICATE OF CONFORMANCE (COC) | | TO MANUFACTURERS SPECIFICATIONS |
| CUSTOMIZED SPECIAL DIALS | | TONS-ON-RAM, ETC. (per scale) |
| RUBBER CASE PROTECTORS - 2.5 inch | | INSTALLED |
| | | NOT INSTALLED |
| RUBBER CASE PROTECTORS - 4 inch | | INSTALLED |
| | | NOT INSTALLED |
| 10-32 UNF 2 B FEMALE CONN. | | BRASS CONNECTION |
| | | STAINLESS STEEL CONNECTION |
| 1/4" NPT x G 1/4 Adaptor | | BRASS |
| SEALING GASKET | | |
| DRY OUT CHARGE FOR 900 SERIES GAUGES | | 300 SERIES GAUGES NO CHARGE |
| MAGNETIC SPRING CONTACT SWITCH (MSCS) PRE-WIRED WITH 5' CABLE AND CONNECTOR (SHIELDED 4-WIRE CABLE) | | AVAILABLE ON MODELS 40-400, 40-410 40-901 (Dry), 40-911 (Dry) RANGES FROM 0-60 psi THROUGH 0-30,000 psi |

STANDARD NOSHOK ORIFICES

| RESTRICTION DIMENSION | MATERIAL | PART NO. |
|--|----------|-------------|
| Sintered (20 Micron) Press Fit | BRASS | B-C-000 |
| 0.1 mm Press-Fit | BRASS | B-P-001 |
| 0.3 mm Press-Fit | BRASS | B-P-003 |
| 3.5M x 0.2 mm Threaded | BRASS | B-T-352 |
| 3.5M x 0.3 mm Threaded | BRASS | B-T-353 |
| 3.5M x 0.5 mm Threaded | BRASS | B-T-355 |
| 0.8 mm Press-Fit | BRASS | B-P-008 |
| 4M x 0.3 mm Threaded | BRASS | B-T-403 |
| 4M x 0.4 mm Threaded | BRASS | B-T-404 |
| 4M x 0.8 mm Threaded | BRASS | B-T-408 |
| 0.4 mm Press-Fit | 316 SS | S-P-004 |
| 4M x 0.3 mm Threaded with (14 mm Extension) | 316 SS | S-T-403-14E |
| 4M x 0.5 mm Threaded | 316 SS | S-T-405 |
| 4M x 0.8 mm Threaded | 316 SS | S-T-408 |

CLEANING FOR OXYGEN SERVICES

| DESCRIPTION | 1 - 5 Pcs | 6 - 10 Pcs | 11 - 25 Pcs |
|---|-----------|------------|-------------|
| 1" - 2.5" Diameter Up to 1,000 psi | | | |
| 1,500 psi & Up | | | |
| 4" - 6" Diameter Up to 1,000 psi | | | |
| 1,500 psi & Up | | | |
| CERTIFICATE OF CLEANING: \$12.23 IMMEDIATE RESPONSE SERVICE ADD 20% LIQUID FILL GAUGES MUST HAVE HALOCARBON® (FLUORO-CHEMICAL) FILL ONLY Above prices apply to new gauges only, used gauges are cleaned on a per quotation basis. | | | |

GAUGE FILL OPTIONS

| | VOLUME | SILICONE | HALOCARBON® | -40° SERVICE | MINERAL OIL |
|----------------|--------|----------|-------------|-----------------------|--------------------|
| 300 SERIES | OZ | D.C. 200 | 4.2 OIL | GLYCERINE: H2O (d) | LIGHT VISCOSITY |
| 25-300/25-310 | 2.0 | | | | |
| 40-300/40-310 | 6.5 | | | | |
| 500 SERIES | | | | | |
| 25-500/25-510 | 2.0 | | | | |
| 40-500/40-510 | 8.5 | | | | |
| 60-500/60-510 | 31.0 | | | | |
| 600/700 SERIES | | | | | |
| 45-660/45-760 | 14.0 | | | | |
| 900 SERIES | | | | | |
| 25-900/25-910 | 2.0 | | | | |
| 25-901/25-911 | 2.0 | | | | |
| 40-901/40-911 | 8.5 | | | | |