



NOSHOK, INC.

1010 W. Bagley Road

Berea, OH 44017

Phone: 440.243.0888

Fax: 440.243.3472

Website: www.noshok.com

625/626 Series Intrinsically Safe Pressure Transmitters

- Low pressure ranges for vapor recovery applications, vacuum and compound ranges through 0 psig to 15,000 psig; absolute ranges from 0 psia to 15 psia through 0 psia to 300 psia
- Current output
- 316 and 14-4PH Stainless Steel wetted parts



1 2 3

Full Scale

Part Number	Description	Pressure Range	Best Fit Straight Line	Process Connections	Electrical Connection
<u>625-5000-1-1-2-8</u>	0 to 5,000 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, 1/4" National Pipe Thread (NPT) Male Pressure Transmitter with DIN EN 175301-803 Form A Electrical Connection	0 to 5,000 psig	0.25 %	1/4 in. Male National Pipe Thread (MNPT)	DIN EN 175301-803 Form A
<u>625-5000-1-1-8-8</u>	0 to 5,000 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, 1/2" National Pipe Thread (NPT) Male Pressure Transmitter with DIN EN 175301-803 Form A Electrical Connection	0 to 5,000 psig	0.25 %	1/2 in. Male National Pipe Thread (MNPT)	DIN EN 175301-803 Form A
<u>625-500-1-1-8-8</u>	0 to 500 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, 1/2" National Pipe Thread (NPT) Male Pressure Transmitter with DIN EN 175301-803 Form A Electrical Connection	0 to 500 psig	0.25 %	1/2 in. Male National Pipe Thread (MNPT)	DIN EN 175301-803 Form A
<u>625-5-1-1-8-8</u>	0 to 5 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, 1/2" National Pipe Thread (NPT) Male Pressure Transmitter with DIN EN 175301-803 Form A Electrical Connection	0 to 5 psig	0.25 %	1/2 in. Male National Pipe Thread (MNPT)	DIN EN 175301-803 Form A




Need Help?


Click here and start chatting with us!

Chat now



Part Number	Description	Pressure Range	Full Scale Best Fit Straight Line	Process Connections	Electrical Connection
<u>625-60-1-1-8-8</u>	0 to 60 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, 1/2" National Pipe Thread (NPT) Male Pressure Transmitter with DIN EN 175301-803 Form A Electrical Connection	0 to 60 psig	0.25 %	1/2 in. Male National Pipe Thread (MNPT)	DIN EN 175301-803 Form A
<u>625-60-2-1-8-1-50</u>	0 to 60 psig, 0.125% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, 1/2" National Pipe Thread (NPT) Male Pressure Transmitter with DIN EN 175301-803 Form A with 50' Cable Electrical Connection	0 to 60 psig	0.125 %	1/2 in. Male National Pipe Thread (MNPT)	DIN EN 175301-803 Form A with 36" Cable
<u>625-7500-1-1-2-25</u>	0 to 7,500 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, 1/4" National Pipe Thread (NPT) Male Pressure Transmitter with M12 x 1 (4 Pin)	0 to 7,500 psig	0.25 %	1/4 in. Male National Pipe Thread (MNPT)	M12 x 1 (4-Pin) Ingress Protection (IP67)
<u>625-7500-1-1-8-25</u>	0 to 7,500 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, 1/2" National Pipe Thread (NPT) Male Pressure Transmitter with	0 to 7,500 psig	0.25 %	1/2 in. Male National Pipe Thread (MNPT)	M12 x 1 (4-Pin) Ingress Protection (IP67)

Part Number	Description	Pressure Range	Full Scale Best Fit Straight Line	Process Connections	Electrical Connection
					
M12 x 1 (4 Pin)					
<u>625-7500-1-1-8-8</u>	0 to 7,500 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, 1/2" National Pipe Thread (NPT) Male Pressure Transmitter with DIN EN 175301-803 Form A Electrical Connection	0 to 7,500 psig	0.25 %	1/2 in. Male National Pipe Thread (MNPT)	DIN EN 175301-803 Form A
<u>626-300-1-1-11-8</u>	0 to 300 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, G1/2B Front Flush Pressure Transmitter with DIN EN 175301-803 Form A Electrical Connection	0 to 300 psig	0.25 %	G 1/2 B	DIN EN 175301-803 Form A
<u>626-5000-1-1-11-3</u>	0 to 5,000 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, G1/2B Front Flush Pressure Transmitter with 6-pin Bayonet - IP65 Electrical Connection	0 to 5,000 psig	0.25 %	G 1/2 B	6-Pin Bayonet - Ingress Protection (IP65)
<u>626-750-1-1-11-8</u>	0 to 750 psig, 0.25% Accuracy (Best Fit Straight Line (BFSL), 4 to 20 mA Output, G1/2B Front Flush Pressure Transmitter with DIN EN 175301-803 Form A Electrical Connection	0 to 750 psig	0.25 %	G 1/2 B	DIN EN 175301-803 Form A

Part Number	Description	Pressure Range	Full Scale Best Fit Straight Line	Process Connections	Electrical Connection 
-------------	-------------	----------------	---	---------------------	---



Need Help?

Call 1-800-368-7000 or visit us online at [www.foxvalve.com](#)